This listing of claims will replace all prior versions and listings of claims in this

application:

Listing of Claims

Claim 1 (canceled)

Claim 2 (new): A method of transmitting at least one digital code over a network carrying

AC current comprising:

transmitting a signal corresponding to the code over the AC current network using

the AC current for determining timing of transmission,

wherein, for each code, the signal is a sum of sine waves of several frequencies

with phases selected between 0 and 2π for each frequency,

wherein the same frequencies are used for all codes, and

wherein the set of phases is unique for each code.

Claim 3 (new): The method of Claim 2, wherein the signal for at least one code is

transmitted from storage.

Claim 4 (new): The method of Claim 2, wherein the phases are selected to minimize the

crest factor of the signal.

Claim 5 (new): The method of Claim 2, wherein the phases are selected randomly or

pseudo-randomly between 0 and 2π .

Claim 6 (new): The method of Claim 2, wherein the frequencies are equidistant.

Claim 7 (new): The method of Claim 2, wherein the at least one digital code identifies a

transmitting device.

Claim 8 (new): A method of detecting transmission at least one digital code over a

network carrying AC current comprising:

4 of 6

Application No.: 10/578,116 Amendment dated: May 14, 2009

Reply to Office Action of January 14, 2009 Attorney Docket No.: 0155.0002US1

for each code, determining a phase ϕ_i between 0 and 2π for each of several frequencies f_i so that the set of phases is unique for each code;

receiving a signal over the AC current network using the AC current for determining timing of transmission;

for each frequency f_i determining a complex Fourier coefficient of the signal C_i; calculating a sum by adding for each pair (i, i-1)

$$sign(Re(C_{i}\cdot(C_{i-1})*\cdot exp(-j\cdot(\varphi_{i}-\varphi_{i-1}))));$$
 and

detecting the digital code when the sum is higher than a threshold.

Claim 9 (new): The method of Claim 8, wherein the phases are selected to minimize the crest factor of the signal.

Claim 10 (new): The method of Claim 8, wherein the phases are selected randomly or pseudo-randomly between 0 and 2π .

Claim 11 (new): The method of Claim 8, wherein the frequencies are equidistant.

Claim 12 (new): The method of Claim 8, wherein the at least one digital code identifies a transmitting device.